



STARTER 300D



STARTER

STARTER 300D

STARTER 300D

(CMC)

CE

ISO9001

!



30

15 240



mg/L, % ppm

/

/

10



STARTER 300D

STARTER 300D

STARTER 300D

	%	0.0 ~199.9%; 200 ~ 400%
	mg/L	0.00 ~19.99; 20.0 ~ 45.0mg/L
	ppm	0.00 ~19.99; 20.0 ~ 45.0ppm
	Temp.	0 ~ 50 °C
	%	0.1%; 1%
	mg/L	0.01mg/L; 0.1 mg/L
	ppm	0.01ppm; 0.1 ppm
	Temp.	0.1 °C
	mmHg	375 ~ 825 mmHg
	mbar	500 ~ 1100 mbar
	hPa	500 ~ 1100 hPa
	mmHg	1 mmHg
	mbar	1 mbar
	hPa	1 hPa
		± 1%; ± 0.3 °C
/		0.0 ~ 40.0 ppt, 0.1 ppt
		1 2

STARTER 300D

	4 7 , 6V DC, 5mA, 250
	90 W x 170 D x 35 H mm
	0.18 kg
IP	IP54
	ATC MTC, Cinch , NTC 30 kΩ
	ABS
	PMMA()
	PET
	5-40 °C
	5%-80% ()
	2000